

## Spulen für EV225B



Spannung		Frequenz [Hz]	Wirkleistung [W]			BQ-Spule, a.c. 10 bar, 185 °C IP65 clip	BN-Spule, d.c. 5 bar, 160 °C IP65 clip	BB-Spule, a.c. 5 bar, 160 °C IP65 clip	BB-Spule, d.c. 3.6 bar, 140 °C IP65 clip
[a.c.]	[d.c.]		BQ	BN	BB				
24		50	10		10	<b>018F4517</b>		<b>018F7358</b>	
24		60			10			<b>018F7365</b>	
115		50			10			<b>018F7361</b>	
110		60	10		10	<b>018F4519</b>		<b>018F7360</b>	
220		60	10			<b>018F4520</b>			
230		50	10		10	<b>018F4511</b>		<b>018F7351</b>	
230		60			10			<b>018F7363</b>	
240		50			10			<b>018F7352</b>	
380		50			10			<b>018F7353</b>	
	12				18				<b>018F7396</b>
	24			20	18		<b>018F6968</b>		<b>018F7397</b>

## Kabelstecker, Schutzart IP65



To use with all BB coils

**042N0156**

**042N0156**

**042N0156**

**042N0156**

## Ersatzteilkits



Applikation	Dichtungswerkstoff	Bestellnummer
EV225 6-10	PTFE	<b>032U3171</b>
EV225 15	PTFE	<b>032U3172</b>
EV225 20 -25	PTFE	<b>032U3173</b>